

| HPA SERİSİ ELEKTRİK MOTORLU YAĞ SOĞUTUCULARI | | | | | | |
|--|------------|----------|--------|-------------------------|-----------|-------|
| Tipi | Maks. Debi | Kapasite | Basınç | Motor | Termostat | Fiyat |
| HPA | (lt/dak.) | (kcal/h) | (bar) | Tipi | (°C) | Euro |
| HPA 12 | 120 | 8.000 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 18 | 160 | 13.500 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 24 | 160 | 16.000 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 30 | 160 | 21.500 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 36 | 200 | 30.000 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 42 | 200 | 35.000 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 50 | 280 | 40.000 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |
| HPA 52 | 280 | 43.000 | 20 | 230/400V 3 FAZ 50/60 HZ | 60/48° | |

| HPA SERİSİ ELEKTRİK MOTORLU YAĞ SOĞUTUCULARI | | | | | | |
|--|------------|----------|--------|-------|-----------|-------|
| Tipi | Maks. Debi | Kapasite | Basınç | Motor | Termostat | Fiyat |
| HPA | (lt/dak.) | (kcal/h) | (bar) | Tipi | (°C) | Euro |
| HPA 12 | 120 | 13.500 | 20 | GR 2 | 60/48° | |
| HPA 18 | 140 | 24.000 | 20 | GR 2 | 60/48° | |
| HPA 24 | 140 | 27.500 | 20 | GR 2 | 60/48° | |
| HPA 30 | 160 | 38.000 | 20 | GR 2 | 60/48° | |
| HPA 36 | 180 | 41.000 | 20 | GR 2 | 60/48° | |
| HPA 42 | 220 | 46.000 | 20 | GR 2 | 60/48° | |
| HPA 50 | 280 | 56.000 | 20 | GR 2 | 60/48° | |
| HPA 52 | 280 | 58.000 | 20 | GR 2 | 60/48° | |

***PLM 20 (GR 2) çift yönlü serisi hidromotor fiyatı ilave ediniz.

| MG SERİSİ SULU YAĞ SOĞUTUCULARI | | | | |
|---------------------------------|---------------|----------|--------|-------|
| Tipi | 1,5 Barda | Kapasite | Basınç | Fiyat |
| MG | Debi (lt/dak) | (kcal/h) | (bar) | Euro |
| MG 80.150.4 | 75 | 8.000 | 12 | |
| MG 80.310.4 | 80 | 13.000 | 12 | |
| MG 80.385.4 | 80 | 16.500 | 12 | |
| MG 80.560.4 | 80 | 18.500 | 12 | |
| MG 80.715.4 | 120 | 22.000 | 12 | |
| MG 80.870.4 | 130 | 25.000 | 12 | |
| MG 80.1155.4 | 130 | 29.000 | 12 | |
| MG 81.560.4 | 150 | 23.000 | 12 | |
| MG 81.715.4 | 180 | 25.000 | 12 | |
| MG 81.870.4 | 180 | 28.000 | 12 | |
| MG 130.285.4 | 160 | 28.000 | 12 | |
| MG 130.535.4 | 200 | 42.000 | 12 | |
| MG 130.845.4 | 280 | 58.000 | 12 | |
| MG 130.995.4 | 280 | 63.000 | 12 | |
| MG 130.1105.4 | 280 | 70.000 | 12 | |
| MG 131.521.4 | 280 | 72.000 | 12 | |
| MG 131.831.4 | 400 | 96.000 | 12 | |
| MG 155.520.4 | 300 | 72.000 | 12 | |
| MG 155.830.4 | 380 | 92.000 | 12 | |
| MG 155.1130.4 | 420 | 116.000 | 12 | |
| MG 155.1435.4 | 450 | 132.000 | 12 | |
| MG 155.1730.4 | 450 | 158.000 | 12 | |

| MGB SERİSİ SULU YAĞ SOĞUTUCULARI | | | | |
|----------------------------------|---------------|----------|--------|-------|
| Tipi | 1,5 Barda | Kapasite | Basınç | Fiyat |
| MGB | Debi (lt/dak) | (kcal/h) | (bar) | Euro |
| MGB 80.250.4 | 160 | 13.500 | 12 | |
| MGB 80.500.4 | 180 | 22.000 | 12 | |
| MGB 80.505.4 | 180 | 26.000 | 12 | |
| MGB 80.1110.4 | 200 | 34.000 | 12 | |
| MGB 114.500.4 | 220 | 34.000 | 12 | |
| MGB 114.805.4 | 250 | 40.000 | 12 | |
| MGB 114.1110.4 | 250 | 50.000 | 12 | |
| MGB 114.1415.4 | 280 | 60.000 | 12 | |
| MGB 130.285.4 | 160 | 28.000 | 12 | |
| MGB 130.535.4 | 200 | 42.000 | 12 | |
| MGB 130.845.4 | 280 | 58.000 | 12 | |
| MGB 130.995.4 | 280 | 64.000 | 12 | |
| MGB 130.1105.4 | 280 | 70.000 | 12 | |
| MGB 140.490.4 | 220 | 46.000 | 12 | |
| MGB 140.795.4 | 250 | 65.000 | 12 | |
| MGB 140.1110.4 | 250 | 84.000 | 12 | |
| MGB 140.1405.4 | 280 | 103.000 | 12 | |
| MGB 168.470.4 | 450 | 68.000 | 12 | |

| | | | | |
|----------------|-----|---------|----|--|
| MGB 168.775.4 | 500 | 96.000 | 12 | |
| MGB 168.1080.4 | 550 | 122.000 | 12 | |
| MGB 168.1385.4 | 550 | 140.000 | 12 | |
| MGB 219.1350.4 | 800 | 240.000 | 12 | |