



### HA10VSO-DFR (Basınç ve Yük duyarlı/Load sensing) eksenel pistonlu pompalar

Sizes (cm3)				16/18cm3	28 cm3	45 cm3	71 cm3	100 cm3	140 cm3
Displacement	Vg max . Cm3			18	28	45	71	100	140
Max. Speed	Nmax. rpm			3300	3000	2600	2200	2000	1800
Max. Flow	in Nmax.	qv	L/min	59,4	84	117	156	200	252
	in 1500 r/min.			27	42	68	107	150	210
( P:280 bar)	in Nmax.	Pmax.	Kw	27,7	39	55	73	93	118
Max. Power	in 1500 r/min.			12,6	20	32	50	70	98
( P:280 bar)	in Vg max.	Tmax.	Nm	80,1	125	200	316	445	623
Max. Torque									
Weight		m	Kg	12	15	21	33	45	60
Fiyat USD.-									



### HA10VSO-DFLR (Basınç,Yük ve Güç Regülasyonlu) eksenel pistonlu pompalar

Sizes (cm3)				16/18cm3	28 cm3	45 cm3	71 cm3	100 cm3	140 cm3
Displacement	Vg max . Cm3			18	28	45	71	100	140
Max. Speed	Nmax. rpm			3300	3000	2600	2200	2000	1800
Max. Flow	in Nmax.	qv	L/min	59,4	84	117	156	200	252
	in 1500 r/min.			27	42	68	107	150	210
( P:280 bar)	in Nmax.	Pmax.	Kw	27,7	39	55	73	93	118
Max. Power	in 1500 r/min.			12,6	20	32	50	70	98
( P:280 bar)	in Vg max.	Tmax.	Nm	80,1	125	200	316	445	623
Max. Torque									
Weight		m	Kg	14	17	22	35	47	62
Fiyat USD.-									

Rotary grup



