








Outlet Pressure (bar)	Average outlet flow (l/min)	Inlet Pressure (bar)	Inlet flow (l/min)	Connection	Weight (kg)	Ratio	Model: Steel	Model: Stainless steel	Comments	Models
24 - 800	0.3 - 0.5	20 - 200	2.0 - 8.0	Tube	0.7	1.2 - 7.5	HC1			
24 - 800	0.3 - 2.5	20 - 200	2.0 - 15.0	Tube	1.0	1.2 - 20.0	HC2	HC2W		
24 - 500	0.3 - 2.5	20 - 200	2.0 - 15.0	Manifold NG6/DO3	2.5	1.2 - 20.0	HC3			
24 - 800	0.3 - 2.5	20 - 200	2.0 - 15.0	NG6/DO3	3	1.2 - 20.0	HC5		Double Acting	
26 - 800	0.7 - 5.	20 - 200	2.0 - 35.0	Tube	3.7	1.3 - 9.8	HC4	HC4W		
24 - 800	0.7 - 11.0	20 - 200	2.0 - 15.0	Tube	3.8	1.2 - 20.0	HC2D		Dual Acting	
26 - 800	1.5 - 11.0	20 - 200	5.0 - 70.0	Tube	9.5	1.3 - 8.2	HC6			
24 - 800	11.2 - 56.0	20 - 200	5.0 - 70.0	Tube	20	1.2 - 8.2	HC6D		Dual Acting	
100 - 2000	0.3 - 1.6	20 - 200	2.0 - 14.0	Tube	1.5	5.0 - 20.0	HC7	HC7W		
100 - 2000	0.3 - 1.6	20 - 200	2.0 - 14.0	Tube	5.0	5.0 - 20.0	HC8	HC8W		
220 - 5000	0.3 - 1.8	20 - 200	5.0 - 20.0	Tube	9.9	8.2 - 25.0	HC9			
20 - 800	6.0 - 41.0	20 - 200	5.0 - 70.0	Tube	22.0	1.0 - 10.1	HC6D2	HC6D2W	2 media	

İç yapılarının resmi ve dış ölçüleri
minibooster sitesinde mevcut.



Soldaki minibooster sağdaki sauer den alınma