



ThyssenKrupp



**EN 10395-4 (DIN 2391/C) E235 N ST.37.4 NBK HİDROLİK DEVRE BORULARI**

Dış Çap (mm)	Et Kalınlığı (mm)	Ağırlık (Kg/Mt.)	Çalışma Basıncı (Bar)	Euro.-/Mt.
6	1	0,123	458	
8	1	0,173	330	
8	1,5	0,241	528	
10	1,5	0,314	406	
12	1,5	0,388	330	
12	2	0,493	459	
14	1,5	0,462	277	
15	1,5	0,499	257	
16	2	0,691	330	
16	2,5	0,832	375	
18	1,5	0,611	211	
18	2	0,72	240	
20	2	0,888	257	
20	2,5	1,079	330	
22	2	0,986	232	
25	2,5	1,387	257	
25	3	1,628	315	
28	3	1,851	277	
30	3	1,988	257	
30	4	2,565	355	
35	3	2,368	217	
38	3	2,589	220	
38	4	3,354	272	
42	3	2,885	195	
42	4	3,749	244	

\* Fosfat kaplı ve her iki ucu tapalı,

\* Kimyasal ve Fiziksel test sertifikalı

\* Önemli not :20 boy altındaki alımlarda birim fiyata % 10 ilave edilir.



