



### ZEC NEUTRAL (Şeffaf Beyaz) Pnömatik ve Yağlama Hortumları

ILC code	TEKNİK ÖZELLİKLERİ	ÇAL.BAS.(BAR)	PAT.BAS.(BAR)	MIN.BEND.RADIUS mm	ÇAL. SIC. ARALIĞI	FİYAT Euro.-/mt
30.100.0	POLYAMIDE PA6 <b>4x2,5</b> NEUTRAL	45	180	45	0°C +70°C	
30.120.0	POLYAMIDE PA6 <b>6x4</b> NEUTRAL	50	200	60	0°C +70°C	

ILC code	TEKNİK ÖZELLİKLERİ	ÇAL.BAS. (BAR)	PAT.BAS. (BAR)	MIN. BEND. RADIUS mm	ÇAL. SIC. ARALIĞI	FİYAT Euro.-/mt
30.159.0	POLYAMIDE PA12 SR 4x2 NEUT.	70	280	25	Eksi 20°C +80°C	
30.160.0	POLYAMIDE PA12 SR 4x2,5 NEUT.	48	193	36	Eksi 20°C +80°C	
30.161.0	POLYAMIDE PA12 SR 6x3 NEUT.	70	280	36	Eksi 20°C +80°C	

ILC code	TEKNİK ÖZELLİKLERİ	ÇAL.BAS. (BAR)	PAT.BAS. (BAR)	MIN. BEND. RADIUS mm	ÇAL. SIC. ARALIĞI	FİYAT Euro.-/mt
<b>30.156.0</b>	<b>RILSAN PA11 4x2 NEUTRAL</b>	<b>33</b>	<b>133</b>	<b>16</b>	<b>Eksi 40°C +80°C</b>	
<b>30.156.1</b>	<b>RILSAN PA11 4x2,5 NEUTRAL</b>	<b>23</b>	<b>92</b>	<b>24</b>	<b>Eksi 40°C +80°C</b>	
<b>30.156.3</b>	<b>RILSAN PA11 6x4 NEUTRAL</b>	<b>33</b>	<b>133</b>	<b>25</b>	<b>Eksi 40°C +80°C</b>	

ILC code	TEKNİK ÖZELLİKLERİ	ÇAL.BAS. (BAR)	PAT.BAS. (BAR)	MIN. BEND. RADIUS mm	ÇAL. SIC. ARALIĞI	FİYAT Euro.-/mt
30.157.0	RILSAN PA11 SR 4x2 NEUTRAL	70	280	25	Eksi 40°C +80°C	
30.157.1	RILSAN PA11 SR 4x2,5 NEUTRAL	48	193	36	Eksi 40°C +80°C	
30.157.3	RILSAN PA11 SR 6x3 NEUTRAL	70	280	36	Eksi 40°C +80°C	



### SFT Kelepçeler

Model	Özelliği	Ölçü	Fiyat Euro.-
4	onlu	Q4	
6	onlu	Q6	
8	onlu	Q8	
10	onlu	Q10	
12	dörtlü	Q12	

